

Mannering Colliery

*Environmental Noise Monitoring
September 2018*

*Prepared for
LDO Group*



Noise and Vibration Analysis and Solutions

Global Acoustics Pty Ltd
PO Box 3115 | Thornton NSW 2322
Telephone +61 2 4966 4333
Email global@globalacoustics.com.au
ABN 94 094 985 734

Manning Colliery

Environmental Noise Monitoring September 2018

Reference: 18327_R01


Report date: 25 February 2019

Prepared for

LDO Group
PO Box 174
Rutherford NSW 2330

Prepared by

Global Acoustics Pty Ltd
PO Box 3115
Thornton NSW 2322



Prepared: Jonathan Erasmus
Consultant



QA Review: Jason Cameron
Consultant

Global Acoustics Pty Ltd ~ Environmental noise modelling and impact assessment ~ Sound power testing ~ Noise control advice ~ Noise and vibration monitoring ~ OHS noise monitoring and advice ~ Expert evidence in Land and Environment and Compensation Courts ~ Architectural acoustics ~ Blasting assessments and monitoring ~ Noise management plans (NMP) ~ Sound level meter and noise logger sales and hire

EXECUTIVE SUMMARY

Global Acoustics was engaged by the LDO Group to conduct an attended noise survey around Manning Colliery (MC), an underground coal mine in Manning Park, NSW.

The purpose of the noise survey was to quantify and describe the acoustic environment around the site and compare results with limits specified in the project approval (06_0311). Environmental noise monitoring described in this report was undertaken on 25 September 2018.

MC complied with the relevant day, evening and night approval $L_{Aeq,15 \text{ minute}}$ and $L_{A1,1\text{minute}}$ noise limits at all sites during September 2018. Criteria may not always be applicable due to meteorological conditions at the time of monitoring.

Global Acoustics Pty Ltd

Table of Contents

1 INTRODUCTION.....	1
1.1 Background.....	1
1.2 Monitoring Locations.....	1
1.3 Operations.....	1
1.4 Terminology & Abbreviations.....	3
2 PROJECT APPROVAL & CRITERIA.....	4
2.1 Project Approval.....	4
2.2 Noise Management Plan.....	4
2.3 Project Specific Criteria.....	4
2.4 Modifying Factors.....	6
2.4.1 <i>Tonality and Intermittent Noise</i>	6
2.4.2 <i>Low-Frequency Noise</i>	6
3 METHODOLOGY.....	8
3.1 Overview.....	8
3.2 Attended Noise Monitoring.....	8
3.3 Modifying Factors.....	9
3.4 Monitoring Equipment.....	9
4 RESULTS.....	10
4.1 Total Measured Noise Levels.....	10
4.2 Modifying Factors.....	10
4.3 Atmospheric Conditions.....	12
5 SUMMARY OF COMPLIANCE.....	13

Appendices

A	PROJECT APPROVAL.....	14
B	CALIBRATION CERTIFICATES.....	17

1 INTRODUCTION

1.1 Background

Global Acoustics was engaged to conduct an attended noise survey around Manning Colliery (MC), an underground coal mine at Manning Park, NSW.

Environmental noise monitoring described in this report was undertaken on 25 September 2018.

The purpose of this survey is to quantify and describe the acoustic environment around the site and compare results with specified limits.

1.2 Monitoring Locations

There were three monitoring locations during this survey as detailed in Table 1.1 and shown on Figure 1.

Table 1.1: MC ATTENDED NOISE MONITORING LOCATIONS

Report Descriptor	Monitoring Location
RA1	Pacific Highway, Doyalson
RA2	Macquarie Shores Village, Doyalson North
RA3	Tall Timbers Road, Kingfisher Shores

1.3 Operations

The client has advised that MC was operating during the September 2018 monitoring period.



Figure 1: MC attended noise monitoring locations

1.4 Terminology & Abbreviations

Definitions of terminology and abbreviations, which may be used in this report, are provided in Table 1.2.

Table 1.2: TERMINOLOGY AND ABBREVIATIONS

Descriptor	Definition
L _A	The A-weighted root mean squared (RMS) noise level at any instant
L _{A1,1minute}	The noise level which is exceeded for 1 per cent of the specified time period of 1 minute
L _{A10}	The noise level which is exceeded for 10 percent of the time, which is approximately the average of the maximum noise levels
L _{A90}	The level exceeded for 90 percent of the time, which is approximately the average of the minimum noise levels. The L _{A90} level is often referred to as the “background” noise level and is commonly used to determine noise criteria for assessment purposes.
L _{Aeq}	The average noise energy during a measurement period
L _{pk}	The unweighted peak noise level at any instant
dB(A)	Noise level measurement units are decibels (dB). The “A” weighting scale is used to describe human response to noise.
SPL	Sound pressure level (SPL), fluctuations in pressure measured as 10 times a logarithmic scale, the reference pressure being 20 micropascals.
SEL	Sound exposure level (SEL), the A-weighted noise energy during a measurement period normalised to one second
Hertz (Hz)	Cycles per second, the frequency of fluctuations in pressure, sound is usually a combination of many frequencies together.
VTG	Vertical temperature gradient in degrees Celsius per 100 metres altitude.
SC	Stability Class. Estimated from wind speed and sigma theta data.
Day	This is the period 7:00am to 6:00pm
Evening	This is the period 6:00pm to 10:00pm
Night	The period 10:00pm to 7:00am

2 PROJECT APPROVAL & CRITERIA

2.1 Project Approval

A project approval (06_0311) (the Approval) currently exists for MC. Modification 3 of the Approval specifies the noise requirements in Conditions 1 to 5 of Appendix 4A and Conditions 1 to 4 of Appendix 4B. These sections of the Approval have been reproduced in Appendix A.

2.2 Noise Management Plan

The Noise Management Plan (NMP) for MC was approved on 9 September 2008 by the Department of Planning and Infrastructure. The NMP details the monitoring requirements associated with the operational phase of the mine as well as any ongoing construction activities.

2.3 Project Specific Criteria

Table 1 in Appendix 4B of the Approval details relevant criteria and have been reproduced in Table 2.1.

Table 2.1: MC CRITERIA, dB¹

Location	Day L _{Aeq,15min}	Evening L _{Aeq,15min}	Night L _{Aeq,15min}	Night L _{A1,1min}
4 – Di Rocco	40	40	40	49
5 - Kieghran	43	43	41	49
6 - Swan	42	42	41	49
7 - Druitt	39	39	39	47
8 - May	46	46	46	47
9 - Jeans	41	41	41	51
11 - Jeans	39	39	39	49
18 - Jeans	39	39	39	51
20 – Knight and all other residences	40	40	40	51

Notes:

1. Day: 7:00am to 6:00pm ~ Evening: 6:00pm to 10:00pm ~Night: 10:00pm to 7:00am.

Rural areas and residences have been divided into three receiver areas (and monitoring locations) in the NMP. Table 2.2 outlines the limiting criteria for each monitoring location.

Table 2.2: MC MONITORING LOCATIONS AND LIMITING CRITERIA, dB¹

Location	Day L _{Aeq,15min}	Evening L _{Aeq,15min}	Night L _{Aeq,15min}	Night L _{A1,1min}
RA1	42	42	41	49
RA2	39	39	39	47
RA3	39	39	39	49

Notes:

1. Day: 7:00am to 6:00pm ~ Evening: 6:00pm to 10:00pm ~Night: 10:00pm to 7:00am.

2.4 Modifying Factors

The EPA 'Noise Policy for Industry' (NPfI, 2017) was approved for use in NSW in October 2017, and supersedes the EPA's Industrial Noise Policy (INP, 2000). Assessment and reporting of modifying factors is to be carried out in accordance with Fact Sheet C of the NPfI.

NPfI modifying factors, as they are applicable to mining noise, are described in more detail below.

2.4.1 Tonality and Intermittent Noise

As defined in the NPfI:

Tonal noise contains a prominent frequency and is characterised by a definite pitch.

Intermittent noise is noise where the level suddenly drops/increases several times during the assessment period, with a noticeable change in source noise level of at least 5 dB(A); for example, equipment cycling on and off. The intermittency correction is not intended to be applied to changes in noise level due to meteorology.

2.4.2 Low-Frequency Noise

As defined in the NPfI:

Low frequency noise is noise with an unbalanced spectrum and containing major components within the low-frequency range (10 – 160 Hz) of the frequency spectrum.

The NPfI contains the current method of assessing low-frequency noise, which is a 2 step process as detailed below:

Measure/assess source contribution C-weighted and A-weighted $L_{eq,T}$ levels over the same time period. The low frequency noise modifying factor correction is to be applied where the C-A level is 15 dB or more and:

- where any of the 1/3 octave noise levels in Table C2 are exceeded by **up to and including** 5 dB and cannot be mitigated, a 2 dBA positive adjustment to measured A weighted levels applies for the evening/night period; and*
- where any of the 1/3 octave noise levels in Table C2 are exceeded by **more than** 5 dB and cannot be mitigated, a 5 dBA positive adjustment to measured A weighted levels applies for the evening/night period and a 2 dBA positive adjustment applies for the daytime period.*

Table C2 and associated notes from the NPfi is reproduced below:

Table C2: One-third octave low-frequency noise thresholds.

Hz/dB(Z)	One-third octave $L_{Zeq,15min}$ threshold level												
Frequency (Hz)	10	12.5	16	20	25	31.5	40	50	63	80	100	125	160
dB(Z)	92	89	86	77	69	61	54	50	50	48	48	46	44

Notes:

- dB(Z) = decibel (Z frequency weighted).
- For the assessment of low-frequency noise, care should be taken to select a wind screen that can protect the microphone from wind-induced noise characteristics at least 10 dB below the threshold values in Table C2 for

wind speeds up to 5 metres per second. It is likely that high performance larger diameter wind screens (nominally 175 mm) will be required to achieve this performance (Hessler, 2008). In any case, the performance of the wind screen and wind speeds at which data will be excluded needs to be stated.

- Low-frequency noise corrections only apply under the standard and/or noise-enhancing meteorological conditions.
- Where a receiver location has had architectural acoustic treatment applied (including alternative means of mechanical ventilation satisfying the Building Code of Australia) by a proponent, as part of consent requirements or as a private negotiated agreement, alternative external low-frequency noise assessment criteria may be proposed to account for the higher transmission loss of the building façade.
- Measurements should be made between 1.2 and 1.5 metres above ground level unless otherwise approved through a planning instrument (consent/approval) or environment protection licence, and at locations nominated in the development consent or licence.

3 METHODOLOGY

3.1 Overview

Attended monitoring was conducted in general accordance with Australian Standard AS1055 'Acoustics, Description and Measurement of Environmental Noise' and relevant NSW EPA requirements. Atmospheric condition measurement was also undertaken.

Meteorological data was obtained from the MC meteorological station. This allowed correlation of atmospheric parameters and measured noise levels. Sigma theta is used to calculate vertical temperature gradient (VTG) and Stability Class in accordance with procedures detailed in the NPfI.

3.2 Attended Noise Monitoring

During this survey, monthly attended monitoring was undertaken once at each location during day, evening and night periods. The duration of each measurement was 15 minutes.

Attended monitoring is preferred to the use of noise loggers when determining compliance with prescribed limits as it allows the most accurate determination of the contribution, if any, to measured noise levels from MC.

If the exact contribution of the source of interest cannot be established, due to masking by other noise sources in a similar frequency range, but site noise levels are observed to be well below (more than 5 dB lower than) any relevant criterion, a maximum estimate of the potential contribution of the site might be made based on other measured site-only noise levels, for example, L_{A10} , L_{A50} or L_{A90} . This is generally expressed as a 'less than' quantity, such as <20 dB or <30 dB.

The terms 'Inaudible' (IA) or 'Not Measurable' (NM) may also be used in this report. When site noise is noted as IA, no site noise was audible at the monitoring location. When site noise is noted as NM, this means some noise was audible but could not be quantified. If site noise was NM due to masking but estimated to be significant in relation to a relevant criterion, we would employ methods (e.g. measure closer and back calculate) to determine a value for reporting.

Therefore, all sites noted as NM in this report are due to one or more of the following reasons:

- site noise levels were extremely low and unlikely, in many cases, to be even noticed;
- site noise levels were masked by another relatively loud noise source that is characteristic of the environment (e.g. breeze in foliage or continuous road traffic noise) that cannot be eliminated by moving closer; and/or
- it was not feasible or reasonable to employ NPfI methods such as move closer and back calculate. Cases may include, but are not limited to, rough terrain preventing closer measurement, addition/removal of significant source to receiver shielding caused by moving closer, and

meteorological conditions where back calculation may not be accurate.

A measurement of $L_{A1,1\text{minute}}$ corresponds to the highest noise level generated for 0.6 second during one minute. In practical terms this was quantified by measuring or estimating the highest noise level emitted from a site noise source during the entire measurement period (i.e. the highest level of the worst minute during the 15 minute measurement).

3.3 Modifying Factors

Years of monitoring have indicated that noise levels from mining operations, particularly those measured at significant distances from the source are relatively continuous and broad spectrum. Given this, noise levels from MC at the monitoring locations are unlikely to be intermittent or tonal.

Assessment of low-frequency modifying factors is necessary when application of the maximum correction could potentially result in an exceedance of the relevant site-only L_{Aeq} criterion. Low-frequency analysis is therefore undertaken for measurements in this report where:

- meteorological conditions resulted in criteria being applicable;
- contributions from MC were audible and directly measurable, such that the site-only L_{Aeq} was not “NM” or less than a maximum cut off value (e.g. “<20 dB” or “<30dB”);
- contributions from MC were within 5 dB of the relevant L_{Aeq} criterion, as 5 dB is the maximum penalty that can be applied by low-frequency modifying factors; and
- MC was the dominant low-frequency noise source.

All measurements meeting these conditions were evaluated for possible low-frequency penalty applicability in accordance with the NPfI.

3.4 Monitoring Equipment

Equipment detailed in Table 3.1 was used to measure environmental noise levels. Calibration certificates are provided in Appendix B.

Table 3.1: ATTENDED NOISE MONITORING EQUIPMENT

Model	Serial Number	Calibration Due Date
Rion NA-28 sound level analyser	0071424	05/06/2019
Pulsar 106 acoustic calibrator	74813	05/06/2019

4 RESULTS

4.1 Total Measured Noise Levels

Overall noise levels measured at each location during attended measurement are provided in Table 4.1.

Table 4.2 and Table 4.3 compare measured levels with $L_{Aeq,15\text{minute}}$ and $L_{A1,1\text{minute}}$ criteria detailed in the Approval. Criteria is then applied if weather conditions are in accordance with the Approval and NPfI.

Table 4.1: MEASURED NOISE LEVELS – SEPTEMBER 2018¹

Location	Start Date and Time	L_{A1} dB	L_{A10} dB	L_{A50} dB	L_{Aeq} dB	L_{A90} dB
RA1	25/09/2018 14:33	84	80	72	76	59
RA1	25/09/2018 20:07	80	76	65	71	52
RA1	25/09/2018 22:50	79	68	52	66	37
RA2	25/09/2018 15:24	61	49	40	48	36
RA2	25/09/2018 20:39	40	37	35	35	33
RA2	25/09/2018 22:24	44	37	35	36	33
RA3	25/09/2018 14:59	50	42	36	40	34
RA3	25/09/2018 21:43	40	38	36	37	35
RA3	25/09/2018 22:00	45	39	37	38	35

Notes:

- Noise levels in this table are not necessarily the result of activities at MC.

4.2 Modifying Factors

Measured MC only levels were assessed for the applicability of modifying factors in accordance with the EPA's NPfI.

There were no intermittent or tonal noise sources, as defined in the NPfI, audible from site during the survey. None of the measurements satisfied the conditions outlined in Section 3.3 when assessing low-frequency noise.

Therefore no further assessment of modifying factors was undertaken.

Table 4.2: $L_{Aeq,15minute}$ GENERATED BY MC AGAINST OPERATIONAL NOISE IMPACT ASSESSMENT CRITERIA – SEPTEMBER 2018

Location	Start Date and Time	Wind Speed m/s	VTG °C / 100m ¹	Stability Class	L_{Aeq} Criteria dB	Criteria Applies? ²	MC L_{Aeq} dB ^{3,4}	Exceedance dB ^{4,5}
RA1	25/09/2018 14:33	2.2	-2.0	A	42	Yes	IA	Nil
RA1	25/09/2018 20:07	0.6	3.0	F	42	Yes	IA	Nil
RA1	25/09/2018 22:50	0.5	3.0	F	41	Yes	IA	Nil
RA2	25/09/2018 15:24	2.2	-2.0	A	39	Yes	IA	Nil
RA2	25/09/2018 20:39	1.2	3.0	F	39	Yes	IA	Nil
RA2	25/09/2018 22:24	0.6	3.0	F	39	Yes	IA	Nil
RA3	25/09/2018 14:59	2.7	-2.0	A	39	Yes	IA	Nil
RA3	25/09/2018 21:43	0.4	3.0	F	39	Yes	IA	Nil
RA3	25/09/2018 22:00	0.5	3.0	F	39	Yes	IA	Nil

Notes:

1. Sigma theta data is used to calculate Vertical Temperature Gradient (VTG) and Stability Class in accordance with procedures detailed in the NPfI;
2. In accordance with Appendix 4A of the Approval, noise emission limits do not apply for wind speeds greater than 3m/s at 10 metres above ground level; stability category F temperature inversion conditions and wind speeds greater than 2m/s at 10m above ground level; or stability category G temperature inversion conditions;
3. These are results for MC in the absence of all other noise sources;
4. Bold results in red are those greater than the relevant criterion (if applicable); and
5. NA in exceedance column means atmospheric conditions outside conditions specified in Approval and so criterion is not applicable.

Table 4.3: $L_{A1,1minute}$ GENERATED BY MC AGAINST OPERATIONAL NOISE IMPACT ASSESSMENT CRITERIA – SEPTEMBER 2018

Location	Start Date and Time	Wind Speed m/s	VTG °C / 100m ¹	Stability Class	$L_{A1,1min}$ Criteria dB	Criteria Applies? ²	MC $L_{A1,1min}$ dB ^{3,4}	Exceedance dB ^{4,5}
RA1	25/09/2018 22:50	0.5	3.0	F	49	Yes	IA	Nil
RA2	25/09/2018 22:24	0.6	3.0	F	47	Yes	IA	Nil
RA3	25/09/2018 22:00	0.5	3.0	F	49	Yes	IA	Nil

Notes:

1. Sigma theta data is used to calculate Vertical Temperature Gradient (VTG) and Stability Class in accordance with procedures detailed in the NPfI;
2. In accordance with Appendix 4A of the Approval, noise emission limits do not apply for wind speeds greater than 3m/s at 10 metres above ground level; stability category F temperature inversion conditions and wind speeds greater than 2m/s at 10m above ground level; or stability category G temperature inversion conditions;
3. These are results for MC in the absence of all other noise sources;
4. Bold results in red are those greater than the relevant criterion (if applicable); and
5. NA in exceedance column means atmospheric conditions outside conditions specified in Approval and so criterion is not applicable.

4.3 Atmospheric Conditions

Atmospheric condition data measured by the operator during each measurement using a Kestrel hand-held weather meter is shown in Table 4.4. The wind speed, direction and temperature were measured at approximately 1.8 metres. Attended noise monitoring is not undertaken during rain or hail.

Table 4.4: MEASURED ATMOSPHERIC CONDITIONS – SEPTEMBER 2018

Location	Start Date and Time	Temperature °C	Wind Speed m/s	Wind Direction °MN ¹	Cloud Cover 1/8s
RA1	25/09/2018 14:33	18	1.4	150	4
RA1	25/09/2018 20:07	15	0.0	-	6
RA1	25/09/2018 22:50	14	0.0	-	8
8RA2	25/09/2018 15:24	18	1.1	140	2
RA2	25/09/2018 20:39	13	0.0	-	6
RA2	25/09/2018 22:24	13	0.0	-	8
RA3	25/09/2018 14:59	19	1.0	100	2
RA3	25/09/2018 21:43	16	0.0	-	6
RA3	25/09/2018 22:00	15	0.0	-	8

Notes:

1. "-" indicates calm conditions at 1.8 metres.

Meteorological data from MC weather station was used to determine compliance with specified noise criteria.

5 SUMMARY OF COMPLIANCE

Global Acoustics was engaged by the LDO Group to conduct an attended noise survey around Manning Colliery (MC), an underground coal mine in Manning Park, NSW.

The purpose of the noise survey was to quantify and describe the acoustic environment around the site and compare results with limits specified in the project approval (06_0311). Environmental noise monitoring described in this report was undertaken on 25 September 2018.

MC complied with the relevant day, evening and night approval $L_{Aeq,15 \text{ minute}}$ and $L_{A1,1\text{minute}}$ noise limits at all sites during September 2018. Criteria may not always be applicable due to meteorological conditions at the time of monitoring.

Global Acoustics Pty Ltd

APPENDIX

A PROJECT APPROVAL

NSW Department of Planning Project Approval 06_0311 applies to the MC. The noise section is reproduced below:

**SCHEDULE 3
SPECIFIC ENVIRONMENTAL CONDITIONS**

NOISE

Noise Impact Criteria

1. The Proponent shall ensure that the noise generated by the project does not exceed the noise impact assessment criteria in Table 1 at any residence on privately owned land.

Table 1: Noise limits dB(A)

Day <i>L_{Aeq}(15 min)</i>	Evening <i>L_{Aeq}(15 min)</i>	Night		Location (as listed in Appendix 4)
		<i>L_{Aeq}(15 min)</i>	<i>L_{A1}(1 min)</i>	
49	49	35	49	4 – di Rocco
47	47	35	49	5 – Keighran
44	44	35	49	6 – Swan
43	43	43	50	7 – Druitt
46	46	46	50	8 – May
45	45	45	52	9 – Jeans
40	40	40	52	11 – Jeans
43	43	43	52	18 – Jeans
44	44	44	52	20 – Knight and all other Chain Valley Bay residences

Note: The location of the land referred to in Table 1 is shown on the figure in Appendix 4.

Noise generated by the project is to be measured in accordance with the relevant requirements of the *NSW Industrial Noise Policy* (as may be updated from time-to-time). Appendix 4A sets out the meteorological conditions under which these criteria apply, and the requirements for evaluating compliance with these criteria.

However, these criteria do not apply if the Proponent has an agreement with the owner/s of the relevant residence or land to generate higher noise levels, and the Proponent has advised the Department in writing of the terms of this agreement.

This condition only has effect prior to recommencement of underground coal extraction at Manning Colliery. At all other times, conditions 1 to 4 of Appendix 4B have effect in its place.

Noise Mitigation

2. The Proponent shall prepare a report on potential noise mitigation measures for noisy equipment and activities undertaken on the site to the satisfaction of the **Secretary**. This report must be:
 - (a) prepared by a suitably qualified acoustic expert;
 - (b) submitted to the **Secretary** by the end of September 2008; and
 - (c) accompanied by an action plan for the implementation of any reasonable and feasible recommendations of the report.

Noise Monitoring

3. The Proponent shall prepare a Noise Monitoring Program for the project to the satisfaction of the **Secretary**. This program must:
 - (a) be submitted to the **Secretary** by the end of September 2008;
 - (a1) be revised in consultation with the EPA and be submitted to the **Secretary** by the end of April 2016; and
 - (b) include the use of continuous and attended noise monitoring measures to monitor the performance of the project.

The Proponent shall implement the approved Noise Monitoring Program as approved from time to time by the **Secretary**.

APPENDIX 4A: NOISE COMPLIANCE ASSESSMENT

Applicable Meteorological Conditions

1. The noise criteria in Tables 1 and 2 in Appendix 4B are to apply under all meteorological conditions except the following:
 - (a) wind speeds greater than 3m/s at 10 metres above ground level;
 - (b) stability category F temperature inversion conditions and wind speeds greater than 2 m/s at 10 m above ground level; or
 - (c) stability category G temperature inversion conditions.

Determination of Meteorological Conditions

2. Except for wind speed at microphone height, the data to be used for determining meteorological conditions shall be that recorded by the meteorological station located on the site.

Compliance Monitoring

3. Attended monitoring is to be used to evaluate compliance with the relevant conditions of this approval.
4. This monitoring must be carried out at least once a month (at least two weeks apart) for the first 12 months following recommencement of underground coal extraction, and then quarterly thereafter, unless the Secretary directs otherwise.

Note: The Secretary may direct that the frequency of attended monitoring increase or decrease at any time during the life of the project.

5. Unless the Secretary agrees otherwise, this monitoring is to be carried out in accordance with the relevant requirements for reviewing performance set out in the *NSW Industrial Noise Policy* (as amended from time to time), in particular the requirements relating to:
 - (a) monitoring locations for the collection of representative noise data;
 - (b) meteorological conditions during which collection of noise data is not appropriate;
 - (c) equipment used to collect noise data, and conformity with Australian Standards relevant to such equipment; and
 - (d) modifications to noise data collected, including for the exclusion of extraneous noise and/or penalties for modifying factors apart from adjustments for duration.

APPENDIX

B CALIBRATION CERTIFICATES



**Acoustic
Research
Labs Pty Ltd**

Level 7 Building 2 423 Pennant Hills Rd
Pennant Hills NSW AUSTRALIA 2120
Ph: +61 2 9484 0800 A.B.N. 65 160 399 119
www.acousticresearch.com.au

**Sound Level Meter
IEC 61672-3:2013**

Calibration Certificate

Calibration Number C17248

Client Details Global Acoustics Pty Ltd
12/16 Huntingdale Drive
Thornton NSW 2322

Equipment Tested/ Model Number : Rion NA-28
Instrument Serial Number : 00701424
Microphone Serial Number : 01916
Pre-amplifier Serial Number : 01463

Pre-Test Atmospheric Conditions	Post-Test Atmospheric Conditions
Ambient Temperature : 24.3°C	Ambient Temperature : 24.4°C
Relative Humidity : 40%	Relative Humidity : 39.5%
Barometric Pressure : 100.05kPa	Barometric Pressure : 100kPa

Calibration Technician : Vicky Jaiswal
Calibration Date : 05/06/2017
Secondary Check: Nick Williams
Report Issue Date : 06/06/2017

Approved Signatory :  Ken Williams

Clause and Characteristic Tested	Result	Clause and Characteristic Tested	Result
12: Acoustical Sig. tests of a frequency weighting	Pass	17: Level linearity incl. the level range control	Pass
13: Electrical Sig. tests of frequency weightings	Pass	18: Toneburst response	Pass
14: Frequency and time weightings at 1 kHz	Pass	19: C Weighted Peak Sound Level	Pass
15: Long Term Stability	Pass	20: Overload Indication	Pass
16: Level linearity on the reference level range	Pass	21: High Level Stability	Pass

The sound level meter submitted for testing has successfully completed the class 1 periodic tests of IEC 61672-3:2006, for the environmental conditions under which the tests were performed.

As public evidence was available, from an independent testing organisation responsible for approving the results of pattern evaluation test performed in accordance with IEC 61672-2:2003, to demonstrate that the model of sound level meter fully conformed to the requirements in IEC 61672-1:2002, the sound level meter submitted for testing conforms to the class 1 requirements of IEC 61672-1:2002.

Least Uncertainties of Measurement - Environmental Conditions			
Acoustic Tests		Temperature	±0.05°C
31.5 Hz to 8kHz	±0.16dB	Relative Humidity	±0.46%
12.5kHz	±0.2dB	Barometric Pressure	±0.017kPa
16kHz	±0.29dB		
Electrical Tests			
31.5 Hz to 20 kHz	±0.12dB		

All uncertainties are derived at the 95% confidence level with a coverage factor of 2.



This calibration certificate is to be read in conjunction with the calibration test report.

Acoustic Research Labs Pty Ltd is NATA Accredited Laboratory Number 14172. Accredited for compliance with ISO/IEC 17025.

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports.



**Acoustic
Research
Labs Pty Ltd**

Level 7 Building 2 423 Pennant Hills Rd
Pennant Hills NSW AUSTRALIA 2120
Ph: +61 2 9484 0800 A.B.N. 65 160 399 119
www.acousticresearch.com.au

**Sound Calibrator
IEC 60942-2004**

Calibration Certificate

Calibration Number C17249

Client Details Global Acoustics Pty Ltd
12/16 Huntingdale Drive
Thornton NSW 2322

Equipment Tested/ Model Number : Pulsar 106
Instrument Serial Number : 74813

Atmospheric Conditions

Ambient Temperature : 24.3°C
Relative Humidity : 38.9%
Barometric Pressure : 99.96kPa

Calibration Technician : Vicky Jaiswal
Calibration Date : 05/06/2017

Secondary Check: Nick Williams
Report Issue Date : 06/06/2017

Approved Signatory : 

Ken Williams

Clause and Characteristic Tested	Result	Clause and Characteristic Tested	Result
5.2.2: Generated Sound Pressure Level	Pass	5.3.2: Frequency Generated	Pass
5.2.3: Short Term Fluctuation	Pass	5.5: Total Distortion	Pass

	Nominal Level	Nominal Frequency	Measured Level	Measured Frequency
Measured Output	94.0	1000.0	93.8	1000.33

The sound calibrator has been shown to conform to the class 2 requirements for periodic testing, described in Annex B of IEC 60942:2004 for the sound pressure level(s) and frequency(ies) stated, for the environmental conditions under which the tests were performed.

Least Uncertainties of Measurement -

Specific Tests

Generated SPL ±0.11dB
Short Term Fluct. ±0.02dB
Frequency ±0.01%
Distortion ±0.5%

Environmental Conditions

Temperature ±0.05°C
Relative Humidity ±0.46%
Barometric Pressure ±0.017kPa

All uncertainties are derived at the 95% confidence level with a coverage factor of 2.



This calibration certificate is to be read in conjunction with the calibration test report.

Acoustic Research Labs Pty Ltd is NATA Accredited Laboratory Number 14172.
Accredited for compliance with ISO/IEC 17025.

The results of the tests, calibrations and/or measurements included in this document are traceable to Australian/national standards.

NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, medical testing, calibration and inspection reports.

PAGE 1 OF 1